




HYDRAULIC MULCHING HEAD




The **hydraulic mulching head M3** is designed with a strong and reliable structure and can easily fit all types of excavators. It is manufactured in different models, depending on the use and size of the excavator and is supplied equipped with **cast iron reversible hydraulic motor (hydraulic motor piston for excavators from 7 t), height-adjustable leveling roller, anti-cavitation valve.**



Multipurpose knives for herbs and shrubs max Ø 3 cm. ROTOR A



Slice knives for herbs and shrubs max Ø 3 cm. ROTOR I



Slice knives for herbs, bushes and shrubs max Ø 5 cm. ROTOR C



Lightweight knives for herbs and vine shoots max Ø 1 cm. ROTOR H



Slice knives for herbs, reeds and bushes max Ø 6 cm. ROTOR F



Heavy bat for vine shoots, bushes, reeds and shrubs max 8 cm. ROTOR G



Multipurpose knives for herbs and shrubs max Ø 2 cm. ROTOR O



Floating balancer on request.

TECHNICAL DETAILS

MODEL	Width (mm)	Weight (Kg)	Oil (l/min)	Pressure (bar)	Machine class (t)	Rotor series	Rotor opt.	Motor Displacement (cc)	Motor Type
MTE 60 DXL	600	65	20	160	0,8-2,0	H	--	8	hydraulic cast iron motor
MTE 80 DXL	800	85	20	160	1,2-2,0	H	--	8	hydraulic cast iron motor
MTE 80 DL	800	100	25	170	2,0-3,0	O	I	11	hydraulic cast iron motor
MTE 100 DL	1000	120	25	170	2,0-3,0	O	I	11	hydraulic cast iron motor
MTE 80 DP	800	170	30-35	180	3,0-7,0	A	C	14	hydraulic cast iron motor
MTE 100 DP	1000	195	40-45	180	3,0-7,0	A	C	16	hydraulic cast iron motor
MTE 100 CL	1050	315	50-60	220	7,0-12,0	A	C	34	hydraulic piston motor
MTE 120 CL	1250	345	50-60	220	7,0-12,0	A	C	34	hydraulic piston motor
MTE 120 CP	1250	430	85-100	240	12,0-20,0	F	G	47*	hydraulic piston motor
MTE 160 CP	1600	525	85-100	240	12,0-20,0	F	G	47*	hydraulic piston motor

* on demand also available with displacement of 56 cc. Suggested for excavators over 15 t

